


Cfg for specified reboot of H3C core switch



Overview

Support Use the schedule reboot at command to enable the timing reboot function of the switch and set the specific reboot time Support From the left naviga.

Key Takeaways

Use the boot boot-loader primary command to specify the software image for the next reboot, then execute a controlled reboot from system view.Steps to Configure a Specified Reboot

- Access the CLI and Enter System View Log in to the switch and enter system view using: system-view This allows you to configure system-wide settings, including boot parameters.
- Specify the Bootstrap Program Use the boot boot-loader primary command to set the desired application file for the next reboot. For example:
 - For the active SRPU: boot boot-loader primary flash:/S9500-CMW310-r1262.app
 - For a standby SRPU in slot 1: boot boot-loader primary slot1#flash:/S9500-CMW310-r1262.app Ensure the file exists in the CF card or root directory of the Flash memory; otherwise, the configuration will fail .
- Verify the Boot Configuration Use the display boot-loader command to confirm the primary and backup applications set for the next reboot: display boot-loader This will show the current primary and backup APP files for each board .

- Perform a Controlled Reboot To safely reboot the device without risking file system damage, use the following steps:
 - Navigate to the maintenance menu in the Web interface: Device > Maintenance > Reboot
 - Click Reboot Device and confirm by clicking Apply Avoid using a force reboot unless the system is unresponsive, as it bypasses software checks and may damage the file system .
 - Post-Reboot Verification After the switch reboots, re-access the CLI or Web interface to ensure the device has booted the specified image and is functioning correctly.
- Notes and Best Practices
- Always ensure the specified APP file is compatible with your switch model and stored in the correct location.
 - For switches with dual SRPUs, configure both active and standby SRPUs if needed.
 - Avoid force reboot unless necessary; a controlled reboot preserves system integrity.
 - Backup the current configuration before performing a reboot to prevent data loss. By following these steps, you can safely configure an H3C core switch to reboot using a specified software image, ensuring controlled startup and system stability .

Article Content

Support

Use the schedule reboot at command to enable the timing reboot function of the switch and set the specific reboot time

Support

From the left navigation pane, select Device > Maintenance > Reboot. The Reboot configuration page opens. 2. Click Reboot

H3C Switch Command Mastery: Streamlined Configuration

This article provides a hands-on guide to 50+ essential H3C switch commands, revealing hidden shortcuts and best practices

Automatic restart configuration for H3C device

Problem Description customer wants us to configure a Automatic restart configuration. for example, restart at 22:30

H3C Switches Commands: Reset, Trunk, and Basic Commands

Note: The current configuration is saved in the memory of the switch and will not take effect when the switch is

H3C Safety Trick for Remote Changes | Scheduler Reboot Delay

Welcome to H3C Practice Lab – Episode 3! ☐☐ In this episode, we demonstrate how to use the scheduler reboot delay

H3C S3100-52P COMMAND MANUAL Pdf Download | ManualsLib

For example, if the system name of the switch is H3C, the prompt for user view is . Use the undo sysname command to

H3C S3100-52P COMMAND MANUAL Pdf Download | ManualsLib

View and Download H3C S3100-52P command manual online. S3100-52P switch pdf manual download.

How to Master H3C Device Switch Commands: A Comprehensive Guide

Ready to optimize your network management? Explore our comprehensive guide to H3C device switch commands.

H3C-S5130 switch configuration record sheet

Enter the command: restore factory-default restore factory configuration, clean up operating data Note: After

Knowledge Base

You can restore the factory settings in the CLI as follows: Method 1: 1. Use the reset save command to clear the

H3C S5830V2 COMMAND REFERENCE MANUAL Pdf

View and Download H3C S5830V2 command reference manual online. Switch Series Fundamentals.

Support

Use the schedule reboot at command to enable the scheduled reboot function and specify a specific reboot time and date. Use the

Support

You can save any configuration to a configuration file so the configuration can survive a reboot. You can also back up configuration

H3C S3100-52P COMMAND MANUAL Pdf Download | ManualsLib

Page 39 Command Manual – System Maintenance and Debugging H3C S3100-52P Ethernet Switch Chapter 3 Device Management

Support

H3C series switches provide a series of configuration commands and command line interfaces for configuring and managing the

[H3C S3100-52P COMMAND MANUAL Pdf Download | ManualsLib](#)

Page 28: Schedule Reboot Regularity Command Manual – System Maintenance and Debugging H3C S3100-52P Ethernet Switch

Support

The .cfg configuration file can be specified as both the main and backup next-startup configuration files. Alternatively, you can use

Support

- Schedule a reboot at the CLI, so the device automatically reboots at the specified time or after the specified period of time.
- Power

H3C Campus Fixed-Port Switches Web-Based Configuration Guide

The H3C Campus Fixed-Port Switches Web-Based Configuration Guide describes the web functions of the H3C Campus Fixed-Port

Support

Use the restore startup-configuration command to download a configuration file from the specified TFTP server to the switch and

Support

Description Use super to switch from the current user privilege level to a specified user privilege level. There are four user privilege

Support

For more information about NTP and PTP, see the network management and monitoring configuration guide for the device. The

Support

The configuration file of core switch CORESW2 is the same as that of CORESW1 except the VLAN IDs, interface numbers, OSPF

Support

Use the restore startup-configuration command to download a configuration file from the specified TFTP server to the switch and

Support

Description Use super to switch from the current user privilege level to a specified user privilege level. There are four user privilege

Support

For more information about NTP and PTP, see the network management and monitoring configuration guide for the device. The

Support

The configuration file of core switch CORESW2 is the same as that of CORESW1 except the VLAN IDs, interface numbers, OSPF

Support

Managing configuration files Overview You can manage configuration files from the CLI or the BootWare menus. The following

Support

The specified configuration file must be a valid .cfg file generated by using either the backup function or the save command, or, if a

Master the Basic Command Configurations of Huawei, H3C, Ruijie,

As technology advances, networking switches have become an integral part of the IT infrastructure. They play a

Support

Most configuration commands have an undo form for canceling a configuration, restoring the default, or disabling a feature. For

Support

The Reboot configuration page opens. Figure 1 Reboot configuration page 2. Click Reboot Device. 3. Click Apply in the dialog box

H3C S1600V2 Switch Series Web Configuration Guide

Switch B is connected to the authorized DHCP server through Ethernet port 1, to the unauthorized DHCP server through Ethernet

H3C Campus Fixed-Port Switches CLI-Based Quick Start Configuration ...

If the device has a backup next-startup configuration file, execute the reset saved-configuration backup command to delete the

Basic CLI Commands on H3C Switch

Learn how to create users, VLANs, enable Telnet and SSH, configure Spanning Tree Protocol, enable DHCP snooping, define trunk

Support

You can save any configuration to a configuration file so the configuration can survive a reboot. You can also back up configuration

H3C S5130-HI switch Command Reference

Comprehensive guide to commands for configuring and managing H3C S5130-HI series switches. Covers basic CLI, access control,

Knowledge Base

You can restore the factory settings in the CLI as follows: Method 1: 1. Use the reset save command to clear the

H3C S5830V2 COMMAND REFERENCE MANUAL Pdf

View and Download H3C S5830V2 command reference manual online. Switch Series Fundamentals.

Support

Use the schedule reboot at command to enable the scheduled reboot function and specify a specific reboot time and date. Use the

Support

You can save any configuration to a configuration file so the configuration can survive a reboot. You can also back up configuration

H3C S3100-52P COMMAND MANUAL Pdf Download | ManualsLib

Page 39 Command Manual – System Maintenance and Debugging H3C S3100-52P Ethernet Switch Chapter 3 Device Management

Support

H3C series switches provide a series of configuration commands and command line interfaces for configuring and managing the

H3C S3100-52P COMMAND MANUAL Pdf Download | ManualsLib

Page 28: Schedule Reboot Regularity Command Manual – System Maintenance and Debugging H3C S3100-52P Ethernet Switch

Support

The .cfg configuration file can be specified as both the main and backup next-startup configuration files. Alternatively, you can use

Support

· Schedule a reboot at the CLI, so the device automatically reboots at the specified time or after the specified period of time. · Power

H3C Campus Fixed-Port Switches Web-Based Configuration Guide

The H3C Campus Fixed-Port Switches Web-Based Configuration Guide describes the web functions of the H3C Campus Fixed-Port

Support

Use the restore startup-configuration command to download a configuration file from the specified TFTP server to the switch and

Support

Description Use super to switch from the current user privilege level to a specified user privilege level. There are four user privilege

Support

For more information about NTP and PTP, see the network management and monitoring configuration guide for the device. The

Support

The configuration file of core switch CORESW2 is the same as that of CORESW1 except the VLAN IDs, interface numbers, OSPF

Support

Use the schedule reboot at command to enable the timing reboot function of the switch and set the specific reboot time

Support

From the left navigation pane, select Device > Maintenance > Reboot. The Reboot configuration page opens. 2. Click Reboot

H3C Switch Command Mastery: Streamlined Configuration

This article provides a hands-on guide to 50+ essential H3C switch commands, revealing hidden shortcuts and best practices

Automatic restart configuration for H3C device

Problem Description customer wants us to configure a Automatic restart configuration. for example, restart at 22:30

H3C Switches Commands: Reset, Trunk, and Basic Commands

Note: The current configuration is saved in the memory of the switch and will not take effect when the switch is

H3C Safety Trick for Remote Changes | Scheduler Reboot Delay

Welcome to H3C Practice Lab – Episode 3! ☐☐ In this episode, we demonstrate how to use the scheduler reboot delay

H3C S3100-52P COMMAND MANUAL Pdf Download | ManualsLib

For example, if the system name of the switch is H3C, the prompt for user view is . Use the undo sysname command to

H3C S3100-52P COMMAND MANUAL Pdf Download | ManualsLib

View and Download H3C S3100-52P command manual online. S3100-52P switch pdf manual download.

How to Master H3C Device Switch Commands: A Comprehensive Guide

Ready to optimize your network management? Explore our comprehensive guide to H3C device switch commands.

H3C-S5130 switch configuration record sheet

Enter the command: restore factory-default restore factory configuration, clean up operating data Note: After

Support

Use the schedule reboot at command to enable the timing reboot function of the switch and set the specific reboot time

Support

From the left navigation pane, select Device > Maintenance > Reboot. The Reboot configuration page opens. 2. Click Reboot

H3C Switch Command Mastery: Streamlined Configuration

This article provides a hands-on guide to 50+ essential H3C switch commands, revealing hidden shortcuts and best practices

Automatic restart configuration for H3C device

Problem Description customer wants us to configure a Automatic restart configuration. for example, restart at 22:30

H3C Switches Commands: Reset, Trunk, and Basic Commands

Note: The current configuration is saved in the memory of the switch and will not take effect when the switch is

H3C Safety Trick for Remote Changes | Scheduler Reboot Delay

Welcome to H3C Practice Lab – Episode 3! ☐☐ In this episode, we demonstrate how to use the scheduler reboot delay

H3C S3100-52P COMMAND MANUAL Pdf Download | ManualsLib

For example, if the system name of the switch is H3C, the prompt for user view is . Use the undo sysname command to

H3C S3100-52P COMMAND MANUAL Pdf Download | ManualsLib

View and Download H3C S3100-52P command manual online. S3100-52P switch pdf manual download.

How to Master H3C Device Switch Commands: A Comprehensive Guide

Ready to optimize your network management? Explore our comprehensive guide to H3C device switch commands.

H3C-S5130 switch configuration record sheet

Enter the command: restore factory-default restore factory configuration, clean up operating data Note: After

Contact Us

Continue your research online:

Website: <https://alfa-pro.co.za>

Technical inquiry: <https://alfa-pro.co.za/contact.html>

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

